


Griddle Toaster
























Features:

- · GasMark Certified.
- Piezo & pilot ignition.
- Free standing design.
- Height adjustable feet.
- Full stainless steel body constructed.
- Cabinet style storage space.
- Flame failure safety device.
- Rated at 20^{MJ/hr} per burner.
- Griddle plate thickness: 16mm.
- · Removable: Grease tray. Toaster rack Toaster spillage tray





Specification

Model	Natural Gas	LP Gas	Dimensions (W x D x H)
LKKOB4B+T	40 ^{MJ/h}	40 ^{MJ/h}	600mm x 800mm x 900mm (working height)
LKKOB6A+T	60 ^{MJ/h}	60 ^{MJ/h}	900mm x 800mm x 900mm (working height)

Height including splashback is 1130mm

Accessories: Griddle Grease Tray & 1x Toaster Rack Inlet: Gas: 3/4" BSP

• Specifications and design are subject to change without notice • Pictures are for illustrative purposes only • 2015 July



New Zealand Phone: (+64) 09 837 2960 Fax: (+64) 09 836 9168 (Head Office) 18 Paramount Drive, Henderson, Auckland www.lkk.co.nz sales@lkk.co.nz

Australia

Phone: 1300 655 715 Fax: (+61) 02 8587 0033 47 George St, Clyde Sydney, NSW 2142, Sydney sales@lkk.com.au www.lkk.com.au

Authorised Retailer: